Used Fluid Equipment
Roughneck II™

Balcrank
Fluid Dispensing Systems

The Roughneck II™ drain captures used fluids and transfers them to any bulk storage tank. The unit uses regular shop air and can be pressurized to allow for self-evacuating.

Features

- Patented automatic fluid evacuation valve eliminates gravity draining, pouring, or the need for an evacuation pump, **made in the USA**
- 23 gallon storage tank; fewer drain intervals
- A low pressure safety valve prevents over pressurization of tank.
- Clear evacuation hose; provides fast fluid evacuation and shows fluid levels in tank.

Includes:

- 19.25″ diameter catch basin that features an inlet strainer and s-hooks for tools
- Splashguard bowl design prevents splattering, speeds drainage
- Fully adjustable bowl height from 45" to 72".
- One hand operation. No ball valves required for evacuation of fluid
- Roughneck outlet tube mounts securely into bulk used fluid reservoir
- 7′ evacuation tube provides sight gauge for fluid level
- Tank handle makes maneuvering easy.
- Heavy gauge, all-steel construction guarantees long life
- Tip-resistant balanced design
- Large diameter rear rubber wheels and non-marking wide front casters maneuver the toughest shop floors

TECHNICAL DATA	
Air Pressure Operating Range	5-25 psi (.34-1.72 bar)
Tank Capacity	23 gal (87 l)
Telescoping Range	45"-72" (1.14-1.83 m)
Maximum Pressure	25 psi (1.72 bar)
Pressure Relief Valve	30 psi (2.07 bar)
Air Inlet Size (quick connect)	1/4" NPT
Fluid Outlet Nozzle	1" OD
Estimated Evacuation Time	3 - 4 min.
Wetted Materials	Zinc Plated Steel, Steel, Viton®, HDPE, and PVC
Service Bulletin	SB 4027

MODELS AVAILABLE	DESCRIPTION
4110-022	Roughneck II™ Used Oil Drain
4110-023	Roughneck II™ Used Anti-freeze Drain
4140-064	Replacement Drain Bowl

Liftnow
gov@liftnow.com 1-800-LIFT-NOW
Supplied by Liftnow · liftnow.com